

(19) World Intellectual Property  
Organization  
International Bureau



534 471

(43) International Publication Date  
27 May 2004 (27.05.2004)


PCT

(10) International Publication Number  
WO 2004/044815 A2

- (51) International Patent Classification<sup>7</sup>: G06F 19/00
- (21) International Application Number: PCT/IB2003/004956
- (22) International Filing Date: 3 November 2003 (03.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 102 53 057.2 14 November 2002 (14.11.2002) DE
- (71) Applicant (for DE only): PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Stein-damm 94, 20099 Hamburg (DE).
- (71) Applicant (for all designated States except DE, US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): BORGMANN, Ludger [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (74) Agent: VOLMER, Georg; Philips Intellectual Property & Standards GmbH, Weisshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: DIAGNOSTIC X-RAY SYSTEM



(57) Abstract: The invention relates to a diagnostic X-ray system which comprises notably a mobile X-ray apparatus (10), a mobile data terminal (30) and a data processing unit (20) for the images acquired by means of the X-ray apparatus (10). The system is characterized notably in that the parameters of an X-ray exposure formed by means of the X-ray apparatus (10) are transmitted, preferably in a wireless fashion, to the mobile patient data terminal (30) in which they are combined with patient data entered by a user as well as with an identification number of the image cassette on which the image is stored, read by means of a bar code scanner (306), so as to form a patient data set. Such a patient data set is then transmitted to the data processing unit (20) in which it is supplemented with the image data which is read from the image cassette so as to be processed. It is thus simply possible to combine all relevant data of an X-ray exposure with one another while eliminating any source of errors at least substantially.